

RTD COMPOUND

Page: 1

Compilation date: 10/01/2012

**Revision No: 8** 

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: RTD COMPOUND

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Lubricant for reaming, tapping and drilling.

## 1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

ROCOL House Swillington

Leeds

West Yorkshire LS26 8BS ENGLAND

**Tel:** +44 (0) 113 232 2700

Fax: +44 (0) 113 232 2740

Email: <a href="mailto:customer-service@rocol.com">customer-service@rocol.com</a>

### 1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

#### Section 2: Hazards identification

# 2.1. Classification of the substance or mixture

Classification under CHIP: N: R50/53; -: R64; -: R66

Most important adverse effects: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment. May cause harm to breastfed babies. Repeated exposure may cause skin

dryness or cracking.

## 2.2. Label elements

Label elements under CHIP:

Hazard symbols: Dangerous for the environment.



Risk phrases: R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R64: May cause harm to breastfed babies.

R66: Repeated exposure may cause skin dryness or cracking.

### RTD COMPOUND

Page: 2

Safety phrases: S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

#### 2.3. Other hazards

**PBT:** This substance is not identified as a PBT substance.

#### Section 3: Composition/information on ingredients

#### 3.2. Mixtures

#### **Hazardous ingredients:**

C14-C17 CHLORINATED PARAFFIN - REACH registered number(s): 01-2119519269-33-XXXX

EINECS	CAS	CHIP Classification	CLP Classification	Percent
287-477-0	85535-85-9	N: R50/53; -: R64; -: R66	Lact.: H362; Aquatic Chronic 1: H410	50-70%

#### HIGHLY REFINED MINERAL OIL.

-	64742-62-7	Substance with a Community	-	10-30%
		workplace exposure limit.		

Contains: Mineral oil contains <3% (w/w) DMSO extractable according to IP346

#### Section 4: First aid measures

## 4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so.

### 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Repeated exposure may cause skin dryness or cracking.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be coughing and a sore throat.

## 4.3. Indication of any immediate medical attention and special treatment needed

### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Use water spray to cool containers. Suitable extinguishing media for the surrounding fire

should be used.

## 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

RTD COMPOUND

Page: 3

#### Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

#### 6.4. Reference to other sections

#### Section 7: Handling and storage

## 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

## 7.3. Specific end use(s)

#### Section 8: Exposure controls/personal protection

# 8.1. Control parameters

### Workplace exposure limits:

### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	5ma/m3	10ma/m3	_	_

## **Hazardous ingredients:**

#### HIGHLY REFINED MINERAL OIL.

# Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5mg/m3	10mg/m3	-	-

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not normally required. In case of insufficient ventilation use:

Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Gloves (oil-resistant).

**Eye protection:** Safety glasses with side-shields.

RTD COMPOUND

Page: 4

Skin protection: Protective clothing.Environmental: No special requirement.

### Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

State: Paste
Colour: Brown

Odour: Characteristic odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Flash point°C: >100 Autoflammability°C: >200

Relative density: 1.17

#### 9.2. Other information

Other information: Not applicable.

## Section 10: Stability and reactivity

#### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong reducing agents.

# 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

#### **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

Toxicity values: Not applicable.

#### Symptoms / routes of exposure

Skin contact: Repeated exposure may cause skin dryness or cracking.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

RTD COMPOUND

Page: 5

**Inhalation:** There may be coughing and a sore throat. **Other information:** May cause harm to breastfed babies.

### **Section 12: Ecological information**

### 12.1. Toxicity

### **Ecotoxicity values:**

Species	Test	Value	Units
ALGAE	96H ErC50	>3.2	mg/l
FISH	96H LC50	>5000	mg/l
Daphnia magna	48H EC50	0.006	mg/l

### 12.2. Persistence and degradability

Persistence and degradability: Only slightly biodegradable.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

### 12.4. Mobility in soil

Mobility: Non-volatile. Absorbed only slowly into soil.

### 12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

## 12.6. Other adverse effects

Other adverse effects: No data available.

## Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

### **Section 14: Transport information**

#### 14.1. UN number

UN number: UN3077

# 14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

### 14.3. Transport hazard class(es)

Transport class: 9

RTD COMPOUND

Page: 6

### 14.4. Packing group

Packing group: III

## 14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: Yes

### 14.6. Special precautions for user

Tunnel code: E
Transport category: 3

### **Section 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

### **Section 16: Other information**

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

Compiled in accordance with REACH.

Phrases used in s.2 and 3: H362: May cause harm to breast-fed children.

H410: Very toxic to aquatic life with long lasting effects.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R64: May cause harm to breastfed babies.

R66: Repeated exposure may cause skin dryness or cracking.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.